REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES C	OVERED
1. Addition out their feetre blumy	22 August 1997		eport 1 jun 94 to 31 May 97
4. TITLE AND SUBTITLE		5. F	UNDING NUMBERS
Behavior of Multiphase Granular Media: Modeling the Static-to-Viscous Flow Regime F496920-94-1-0320			
			9F0SRTR 970400
6. AUTHOR(S)			00 01100
John M. Ting			4 FO900
7. PERFORMING ORGANIZATION NAME(S)	AND ADDRESS(ES)		ERFORMING ORGANIZATION
Department of Civil Engineering REPOI			REPORT NUMBER
University of Massachusetts Lov	well		
One University Avenue		1	
Lowell, MA 01854			
9. SPONSORING/MONITORING AGENCY NA	AME(S) AND ADDRESS(ES)		SPONSORING/MONITORING
AFOSR/NA			AGENCY REPORT NUMBER
110 Duncan Ave, Suite B 115			l
Bolling AFB, DC 20332-8050			:
11. SUPPLEMENTARY NOTES		l	
12a. DISTRIBUTION AVAILABILITY STATEM	IFNT	12h	DISTRIBUTION CODE
Approved for Public Release; Distribution Unlimited.			
ripproved for rueste resease,			
13. ABSTRACT (Maximum 200 words)	1 flfootle d	lataalaatia dielee ware gubi	ated to confined compression, they
			eted to confined compression, then
sheared along an interface of varying roughness (very rough or very smooth). Overall, there was excellent comparison			
between the behavior observed in the physical system and the DEM simulations. Global response as measured by external wall forces, and individual particle kinematics were found to be in excellent agreement. Local contact forces and			
interactions were modeled generally well, but not as well as the global behavior.			
interactions were inodeled generally well, but not as well as the global behavior.			
C			
			AE MINAPER OF RACES
14. SUBJECT TERMS			15. NUMBER OF PAGES
			6 16. PRICE CODE
			TO. I MOE GODE
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL



FINAL TECHNICAL REPORT June 1,1996 to May 31, 1997

Behavior of Multiphase Granular Media: Modeling the Static-to-Viscous Flow Regime

John M. Ting

Dept of Civil Engineering
University of Massachusetts Lowell

The original thrust of the research in this AASERT grant was to investigate the solidification of dense fluid suspensions by using Discrete Element Method (**DEM**) simulations. With the changing emphasis within the Particulate Mechanics task in AFOSR, it was decided in January 1996 after consultation and approval from the Interim Program Manager to modify the objectives in the AASERT research. The new thrust involved making extremely careful and controlled comparisons between our DEM analyses and physical interface shear tests data on photoelastic rods conducted by S.G. Paikowsky *et al* as part of their AFOSR-funded research.

In Paikowsky's work, assemblages of nearly perfectly round photoelastic disks were subjected to confined compression, then sheared along an interface of varying roughness (very rough or very smooth). Overall, there was excellent comparison between the behavior observed in the physical system and the DEM simulations. Global response as measured by external wall forces, and individual particle kinematics were found to be in excellent agreement. Local contact forces and interactions were modeled generally well, but not as well as the global behavior.

The details of whether an assemblage is modeled as an assemblage of completely uniform-sized particles, or an assemblage with very slight size variations was found to be a crucial factor in the level of agreement between the physical and numerical systems. In general, even minute variations in particle size can significantly alter the local contact behavior in the DEM simulations. By using a gradation of particle sizes matching the actual observed particle gradation, generally excellent comparisons were made. While it was intended that tests using particles of round as well as ellipse shapes would be compared, the results from the physical tests composed of ellipse shapes were not provided to us.

One US citizen graduate student (Gregory Mischel) was fully supported during his graduate career from this AASERT grant (he received full tuition waivers from UMass Lowell during each semester here, a non-required part of our cost-sharing effort). This student has completed his coursework requirements, is currently finishing his thesis, and should graduate by early fall. As well, one US citizen undergraduate student (Apryl Wilson) was supported for one month this spring on this contract. The grades for both students are satisfactory.

In addition to the research summarized above, Gregory Mischel also participated in a major international collaborative research effort on pressures within silos filled with granular materials, spearheaded by the University of Edinburgh and the UK Engineering and Physical Sciences Research Council. In this *pro bono* collaboration, simulations of silo filling and discharging were conducted using round and ellipse-shaped particles, for comparison with other DEM and Finite Element analyses. These results will be fully documented in Mischel's thesis.

DTIC QUALITY INSPECTED &